



Product Specification Data

DCM 6 MIL PERFORATED VINYL

Facestock: 6 Mil White/Black Perforated 70/30 Vinyl

DCM White/Black 70/30 Perforated Vinyl is a pressure sensitive, window film made from flexible, perforated, vinyl film for use on one-way visual graphic panels. DCM White/Black 70/30 Perforated Vinyl features a 30% open pattern. The composition of the film allows graphics to be printed and viewed from one side. It is recommended that the printed side be edge-sealed to improve the resistance to environmental damage and enhance the durability of the graphic. DCM White/Black 70/30 Perforated Vinyl is specifically designed for architectural window graphics and can be used indoors or outdoors.

Facestock: 6 Mil White/Black Perforated 50/50 Vinyl

DCM White/Black 50/50 Perforated Vinyl is designed for use on one-way visual graphic panels. DCM White/Black 50/50 Perforated Vinyl features a 50% open pattern. The composition of the film allows graphics to be printed and viewed from one side. It is recommended that the printed side be edge-sealed to improve the resistance to environmental damage and enhance the durability of the graphic. DCM White/Black 50/50 Perforated Vinyl is specifically designed for automotive window graphics.

Facestock: 6 Mil Clear Perforated 70/30 Vinyl

DCM Clear 70/30 Perforated Vinyl is designed for use on two-way visual graphic panels. DCM Clear 70/30 Perforated Vinyl features a 30% open pattern. The composition of the film allows graphics to be viewed from both sides. It is recommended that the printed side be edge-sealed to improve the resistance to environmental damage and enhance the durability of the graphic. DCM Clear 70/30 Perforated Vinyl is specifically designed for two-sided window graphics and can be used indoors or outdoors.

Adhesive: Semi-Permanent Acrylic

DCM Perforated Vinyl features a high performance, water-based, acrylic adhesive system which offers durability and environmental stability. The adhesive exhibits excellent cohesive strength and shear resistance. When used with perforated construction, the adhesive exhibits removability from glass surfaces.

The minimum application temperature for DCM Perforated Vinyl is +20°F, with a service temperature range of -40°F to +250°F.

Liner: Custom PET Liner

DCM White/Black 70/30 Perforated Vinyl is sealed onto a customized, 8 mil PET base surface. It is designed to capture and contain excess ink during printing process and features a tight release.

Statement of Practical Use: Per industry standards, all pressure sensitive and non-pressure sensitive materials should be thoroughly tested under actual end-use conditions to ensure that it meets the requirements of the specific application. DCM, Inc. will make no warranty, expressed or implied, pertaining to the functionality or performance of this construction without end user validation, whereby the standard period of warranty will take effect, being one year from purchase date.

